

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72
 Астана +7(7172)727-132
 Белгород (4722)40-23-64
 Брянск (4832)59-03-52
 Владивосток (423)249-28-31
 Волгоград (844)278-03-48
 Вологда (8172)26-41-59
 Воронеж (473)204-51-73
 Екатеринбург (343)384-55-89
 Иваново (4932)77-34-06
 Ижевск (3412)26-03-58
 Казань (843)206-01-48








Калининград (4012)72-03-81
 Калуга (4842)92-23-67
 Кемерово (3842)65-04-62
 Киров (8332)68-02-04
 Краснодар (861)203-40-90
 Красноярск (391)204-63-61
 Курск (4712)77-13-04
 Липецк (4742)52-20-81
 Магнитогорск (3519)55-03-13
 Москва (495)268-04-70
 Мурманск (8152)59-64-93
 Набережные Челны (8552)20-53-41

Нижний Новгород (831)429-08-12
 Новокузнецк (3843)20-46-81
 Новосибирск (383)227-86-73
 Орел (4862)44-53-42
 Оренбург (3532)37-68-04
 Пенза (8412)22-31-16
 Пермь (342)205-81-47
 Ростов-на-Дону (863)308-18-15
 Рязань (4912)46-61-64
 Самара (846)206-03-16
 Санкт-Петербург (812)309-46-40
 Саратов (845)249-38-78

Смоленск (4812)29-41-54
 Сочи (862)225-72-31
 Ставрополь (8652)20-65-13
 Тверь (4822)63-31-35
 Томск (3822)98-41-53
 Тула (4872)74-02-29
 Тюмень (3452)66-21-18
 Ульяновск (8422)24-23-59
 Уфа (347)229-48-12
 Челябинск (351)202-03-61
 Череповец (8202)49-02-64
 Ярославль (4852)69-52-93

сайт: <https://itron.nt-rt.ru/> || эл. почта ino@nt-rt.ru

Diaphragm Meter Product Line

	Model	Temperature Compensation	MAOP*	Available HUB Sizes	Center-to-Center Distance	Capacity (Natural Gas)	Shipping Weight
	I-250	TC & NTC	5 PSIG 10 PSIG (opt.)	10 LT, 1A Sprague, 1-1/4" (1" Pitts), 20 LT, 30 LT	6"	250 CFH @ .5" w.c.diff	9.5 lbs.
	METRIS 250	TC & NTC	5 PSIG 10 PSIG (opt.)	10 LT, 1A Sprague, 1-1/4" (1" Pitts), 20 LT, 30 LT	6"	250 CFH @ .5" w.c.diff	9 lbs.
	METRIS RM (regulator & meter)	TC & NTC	5 PSIG 10 PSIG (opt.)	Inlet: 3/4" or 1" Back Outlet: 10 LT, 1A Sprague/standard, 1-1/4" (1" Pitts), 20LT, 30 LT	NA	250 CFH @ .5" w.c.diff	14.5 lbs.
	400A	TC & NTC	10 PSIG 25 PSIG (opt.)	20 LT, 30 LT, 45 LT, #4 Sprague	6-25/32", 7", or 8 1/4"	400 CFH @ .5" w.c.diff	14.1 lbs.
	675A**	TC & NTC	25 PSIG	30 LT, 45 LT, #4 Sprague	10"	790 CFH @ .5" w.c.diff 1675 CFH @ 2" w.c.diff	41.5 lbs.
	800A**	TC & NTC	25 PSIG	30 LT, 45 LT, 60 LT, 100 LT, #5 Sprague	11"	890 CFH @ .5" w.c.diff 1930 CFH @ 2" w.c.diff	41.5 lbs.
	1000A**	TC & NTC	25 PSIG	45 LT, 60 LT, 100 LT, #5 Sprague	11"	1040 CFH @ .5" w.c.diff 2215 CFH @ 2" w.c.diff	41.5 lbs.

*Maximum allowable operating pressure

**Available with the standard or ET top.